

# SPARK GENERATOR

## ACHIEVE SELF SUSTAINABILITY





# TotleSpark

VICTRON AND MASTERVOLT COMPATIBLE ELECTRIC START / 5 KW

	QUANTITY	UNITY
GENERATOR	Frequency (HZ)	50
	Max. output (Kw)	5
	Rated output (Kw)	4.6
	Rated AC voltage (V)	Single phase 230V
	Power Factor	1
	DC output (V)	12V / 8.3A
	Alternator type	Self-excited, 2-pole, single alternator
	Starting system	Electric
	Noise level (Dba/7m)	68-72 Db
	Fuel tank capacity (L)	15
	Continuous running time (hr)	9
ENGINE	Engine model	SE186FAE
	Engine type	Single cylinder, vertical, 4 stroke aircooled, Diesel
	Bore x Stroke	86 x 72
	Fuel consumption rate (g/kw/h)	≤280
	Fuel	0# or -10# light diesel oil
	Lubrication oil volume (L)	1.65
	Combustion system	Direct injection
STANDARD FEATURES	HJ301 display panel	Yes
	AC output socket	2
	AC circuit breaker	Yes
	Oil warning light	Yes
	Oil alert	Yes
DIMENSIONS	Lenght x Width x Height (mm)	960 x 540 x 760
	Net weight (Kgs)	165
	20ft /40ft container loading pcs	72/144